

WE WEIGH EVERYTHING

B1 SERIES

Weighing indicator



INFORMATION

Units	kg/lb
Accuracy class	III
Division	1/2/5/10/20/50
Signal output ranges	-15MV~15MV
Loadcell connection	Can connect 1-4 pcs 350Ωload cells

FUNCTIONS

- Counting
- Animal weighing
- Hold
- Accumulation

MODELS

MODELS

B1C Weighing Indicator

SPECIFICATIONS

Optional

Bluetooth function, connection, Current loop output

Accuracy

Verified counts: 3000, max external counts:30000,max internal counts:3000000

Standard

Host Computer, Instruction manual, Warranty Card, Eligible certificate, scale top pan, battery

- LCD display
- Plastic Housing
- High precision A/D conversion, Readability is 1/30000
- Zero position tracking range and zero setting (boot/manual) range can be set respectively
- Digital filtering speed, amplitude and the stable time can be set
- Weighing counting function
- Backlight models is optional
- Rechargeable; With under voltage alarm and protection
- With 3.7V/ 4 Ah maintenance-free rechargeable battery.
- A/D conversion mode: Σ - Δ conversion mode
- A/D conversion rate: 10t/S
- Maximum A/D conversion: 24bit
- input signal range:-15MV-15MV
- input sensitivity: $\geq 1 \mu V/e$
- Load cell excitation power: DC3.3v.

