STARTING **CHECK LEVEL**

ENGINE OIL

2 **CHECK GASOLINE LEVEL**

3 **UNPLUG ELECTRIC DEVICES**

FUEL ON 5 **CLOSE CHOKE** 6 **ENGINE SWITCH** ON.



100x33mm

8 **OPEN CHOKE**

90x46mm

AVOID OTHER HAZARDS. READ MANUAL BEFORE USE

DO NOT OPERATE IN A HAZARDOUS LOCATION. SUCH AREAS INCLUDE WHERE THERE IS A RISK OF EXPLOSION OF PETROL FUMES, LEAKING GAS OR EXPLOSIVE DUSTS.

DO NOT OPERATE IN A CONFINED AREA WHERE EXHAUST GASES, SMOKE OR FUMES COULD REACH DANGEROUS CONCENTRATIONS.

DO NOT REFUEL WHILE ENGINE IS RUNNING

THIS MACHINE IS NOT WEATHERPROOF AND SHOULD NOT BE EXPOSED TO DIRECT SUNLIGHT, HIGH AMBIENT TEMPERATURE OR DAMP, WET OR HIGH HUMIDITY CONDITIONS.

HIGHLY FLAMMABLE - NO SMOKING OR NAKED FLAMES NEAR THE GENERATOR.

TAKE EXTRA CARE NOT TO SPILL FUEL. WHEN REFUELLING THE ENGINE ENSURE THAT THE ENGINE HAS BEEN SWITCHED OFF AND THAT ALL PARTS HAVE BEEN ALLOWED TO COOL PREVENT THE SPILLING OF FUEL AS THIS MAY ALSO IGNITE WITH A HOT ENGINE. NEVER REFUEL WHILE THE ENGINE IS RUNNING.

40x37mm



ATTENTION

PLEASE CHECK THE OIL LEVEL BEFORE USE. **INSUFFICIENT OIL WILL** CAUSE ENGINE DAMAGE.

51mm

90x33mm

$oldsymbol{\Delta}$ danger

Using an engine indoors CAN KILL YOU IN MINUTES. Engine exhaust contains carbon monoxide. This is a poisonous gas that you cannot see or sm



NEVER use inside a home or garage, EVEN IF doors and windows are open.



Only use OUTSIDE and far away from windows, doors, and vents.

CHECK FOR ANY SPILT OR LEAKED FUEL

USE ONLY CLEAN, FRESH NON-ETHANOL 95+ UNLEADED



31x31mm

71x22mm

AIR CLEANER MAINTENANCE

■ CLEAN ELEMENT EVERY 50 HOURS (EVERY 10 HOURS UNDER DUSTY CONDITIONS). WASH
IN HIGH FLASH-POINT SOLVENT. SQUEEZE
DRY. THEN DIP IN CLEAN ENGINE OIL AND
SQUEEZE OUT ANY EXCESS OIL.

60x25mm

AIR FILTER

CLEAN FILTER REGULARLY (SEE MANUAL FOR INSTRUCTIONS)

TO OPEN:
NCLIP LATCHES AND REMOVE PLASTIC COVER

76x30.5mm





60x60mm



60x60mm

